



## AZUD modular 100

Our range of manual filters manufactured in technical plastic guarantees the quality of filtered water for lower flow rates in disc and screen technologies.

Nuestra gama de filtros manuales fabricada en plástico técnico garantiza la calidad del agua filtrada para bajos caudales en tecnologías de discos y malla.

### Benefits we provide

- ✔ Equipped with **auxiliary connections**.
- ✔ **Easy handling**. No tools required for maintenance.
- ✔ **Threaded closure system**, easy and safe.
- ✔ **Sealing gasket** in the lid.

### Qué beneficios aportamos


- ✔ Equipado con **conexiones auxiliares**.
- ✔ **Fácil manipulación**. Sin necesidad de herramientas.
- ✔ **Sistema de cierre roscado** fácil y seguro.
- ✔ **Junta de estanqueidad** alojada en la tapa del filtro.


### Standard filtration degrees Grados de filtrado estándar

#### Discs / Discos


 130 micron.  
(120 mesh)

#### Screen / Malla

 530 micron.  
(35 mesh)

 200 micron.  
(75 mesh)

 130 micron.  
(120 mesh)

 100 micron.  
(150 mesh)

✔ AZUD MODULAR 100 is a range of lower flow disc and screen filters. Manufactured in plastic which ensures easy maintenance, high resistance and durability. Flows up to 25 m<sup>3</sup>/h (110 gpm).

✔ AZUD MODULAR 100 es la gama de filtros fabricados en material plástico que asegura un fácil manejo, alta resistencia y durabilidad para caudales de hasta 25 m<sup>3</sup>/h (110 gpm).





Low flow manual filters  
Filtros de limpieza manual para bajos caudales

208

Diameter Diámetro	Max. flow Caudal máx.		Box Caja	un/box* un/caja*	Discs Discos	Code Código 130 micron**	Screen Malla	Code Código 130 micron**
	m³/h	gpm						
3/4" BSP	5	22	AR	60		17L1A120		17L1A220
			2V	10		17L1A122		17L1A222
1" BSP	6	26	AR	60		17L1B120		17L1B220
			2V	10		17L1B122		17L1B222
1 1/4" BSP	10	44	AR	25		17L1C120		17L1C220
			2V	4		17L1C122		17L1C222
1 1/2" BSP	14	62	AR	25		17L1D120		17L1D220
			2V	4		17L1D122		17L1D222
1 1/2" SUPER BSP	20	88	AR	13		17L1E120		17L1E220
			2V	2		17L1E122		17L1E222
2" BSP	25	110	AR	13		17L1F120		17L1F220
			2V	2		17L1F122		17L1F222

\*For filtration degrees different to 130 micron, only available in 2V box. / Para grados de filtrado distintos a 130 micron, solo disponible en caja 2V.

\*\*Ask for other filtration degrees. / Consulte otros grados de filtrado.

530 micron only available from 1 1/4" BSP / 530 micron solo disponible a partir de 1 1/4" BSP.



Filter available in NPT thread  
Filtro disponible en rosca NPT (ANSI/ASME B1.20.1-1983)

DIAMETERS / DIÁMETROS



3/4" BSP

1" BSP

1 1/4" BSP

1 1/2" BSP

1 1/2" SUPER BSP

2" BSP

